

IN1146

LightPro™ Mobile LED Projector

Part#: IN1146

InFocus
Collaboration That Works

Easy, from the word “Go!”

If you're going mobile, take the InFocus LightPro™ IN1146 with you. Our smallest, lightest and most affordable LED projector also features the longest-lasting light source we've ever offered. At about the size of a paperback book and less than two pounds, the IN1146 is easy to pack in your bag and carry on.

Better still, this lampless model makes maintenance easy—or nonexistent—with a light-emitting diode (LED) that lasts up to 30,000 hours. So you can go from place to place, presentation to presentation, without ever giving your projector a thought.



Why choose the LightPro IN1146?

- 30,000-hour LED light source
- Only 1.8 pounds (0.9 kg)
- WXGA (1280 x 800) widescreen resolution
- Excellent connectivity:
 - HDMI and VGA inputs
 - PC-less presentation via USB drive or SD card
 - Optional USB wireless connectivity
- Striking image quality and contrast
- Auto keystone correction
- Built-in stereo speakers

Long-lived lampless light

How long will the light source of IN1146 LED projector really last? The LED is rated for up to 30,000 hours—so if you use it 4 hours a day, 5 days a week, 50 weeks a year, it'll last about 12 years. Until then, it's maintenance-free—not even a filter to clean or replace. And LED projectors even use less power than their conventional cousins, so you can feel more “green” too.



Striking color and contrast

LED projectors are known for their image stability and saturated colors. But the IN1146 features a high contrast of 10,000:1, so it's even better at vividly rendering fine detail and subtle color differences. Even ho-hum business graphics and content pop on the screen.



10,000:1

Connectivity

| | |
|--------------|--|
| HDMI | USB Type A |
| VGA | 3.5 mm composite video/stereo audio in |
| SD Card Slot | 3.5 mm audio out |

Three presentation options

The IN1146 gives you three easy ways to connect. You can present content from your PC over a HDMI or VGA cable. Or forget the cable and connect wirelessly using your laptop and our optional USB WiFi adapter. Or forget the laptop and dynamically display PowerPoint presentations, Word documents, photos, videos and more from a USB thumb drive or SD card.



Ultra-simple operation

When giving a presentation, you don't want to focus on your projector too. The IN1146 is ready when you are. You don't even have to wait for it to warm up: it's on when you flip the switch. And auto keystone correction keeps your image square and true wherever you're projecting.



Auto Keystone Correction

Specifications*

IN1146

| | |
|--|--|
| Native Resolution | WXGA (1280 × 800) |
| Technology | DLP® with LED light source |
| LED Life | 30,000 hours |
| Brightness | 1000 lumens |
| Contrast Ratio | 10,000:1 |
| Aspect Ratio | 16:10 native, 16:9 and 4:3 compatible |
| Input Connections | HDMI, VGA, USB Type A (PC-less display, optional wireless), SD card slot (storage), 3.5 mm composite video/stereo audio in |
| Output Connections | 3.5mm audio out |
| Media File Types (via USB drive or SD card) | Video: AVI, MKV, TS, DAT, VOB, MPG, MPEG, MOV, MP4, 3GP, RM, RMVB, WMV. Photo: JPEG, JPG, BMP. Document: DOC, DOCX, PPT, PPTX, XLS, XLSX, PDF. Music: MP3, WMA, OSG, WAV, AAC |
| Throw Distance | 23.6 - 213 in (0.6 - 5.4 m) |
| Throw Ratio | 1.4:1 |
| Image Width | 20 - 180 in (native 16:10) |
| Digital Zoom Ratio | 1.7:1 |
| Keystone Correction | ± 40° vertical |
| Video Compatibility | SDTV (NTSC, NTSC 4.43, PAL / M / N, SECAM, PAL60", 480i/p, 576i/p), HD (720p, 1080i) |
| H~Synch Range | 30.5 - 91.1 KHz |
| V~Synch Range | 50 - 85 Hz |
| Product Weight | 1.8 lbs (0.8 kg) |
| Product Dimensions - W × D × H | 6.9 × 5.4 × 1.8 in (175 × 138 × 44.5 mm) |
| Shipping Weight | 4.5 lbs (2 kg) |
| Shipping Dimensions - W × D × H | 13 × 8.7 × 4.3 in (330 × 220 × 110 mm) |
| Speaker | 2 W × 2 |
| Power Consumption | 90 W (typical), < 0.5 W (standby) |
| Audible Noise | 32 dBA typical, 34 dBA maximum |
| Power Supply Range | 100V - 240V @ 50-60 Hz (85W) |
| Operating Temperature | 32 - 104° F (0 - 40° C) max |
| Operating Altitude | 0-7,500 feet @ 104° F / 7,500-10,000 feet @ 95° F |
| Operating Humidity | 10~85% RH without condensation |
| Standard Accessories | VGA cable, carry bag, AC power adaptor, Remote control (no batteries), Documentation |
| Safety Certifications | FCC (US/Canada), CE (Europe), CB |
| OSD Languages | English, French, German, Spanish, Italian, Portuguese, Russian, Swedish, Dutch |


* Product specifications, terms, and offerings are subject to change at any time without notice.

Optional Accessories

- Wireless USB module (SP-WIFIUSB-2)
- Presenter RF Remote with USB Receiver
(HW-PRESENTER-2)
- Security Lock (SEC-LOCK-01)
- Extended warranties
(PROJ-EW1YR-MC, PROJ-EW2YR-MC)
- Cables and adapters
- Projection screens

Warranty

The IN1146 projector comes standard with a 1-year warranty and a 90-day accessories warranty. Extended product warranty programs are available.



IN1146
Remote Control

