





Document Manager

- B&W A3 MFP with colour scan function to cover the needs of modern offices.
- Intuitive user interface for quick and easy access to all features.
- Professional high-quality document output thanks to various finishing options.
- Equipped with the Toshiba Secure HDD for enhanced data security.
- Optimised power consumption for highest eco-efficiency.



E:STUDIO357 **E**:STUDIO457 **E**:STUDIO507













complies with IEC6022-1. Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2014 Toshiba TEC. DS507_GBIDD_1405 This Class 1 laser product We are constantly making

E-STUDIO357 E-STUDIO 457 **€**-STUDIO 507

General	Print & Copy Speed Warm-up Time Paper Size & Weight

Paper Capacity Automatic Duplex Inner Output Tray Controller Type Control Panel Memory Interface

Dimensions (W x D x H) Weight

35/45/50 ppm (A4), 25/25/25 ppm (A3) Approx. 20 seconds

Cassettes: A5R-A3, 64-105 g/m² Large Capacity Feeder¹⁾: A4, 64-105 g/m² Bypass: A5R-A3, 52-209 g/m² 2 x 550 sheets (Cassettes), 100 sheets (Bypass) Max. 3.200 sheets

A5R-A3, 64-105 g/m² 250-sheet capacity with offset function Toshiba e-BRIDGE

9" (22.8 cm) colour touch panel LCD Toshiba Secure HDD 320 GB²⁾ / 2 GB RAM 10/100/1000 BaseT (incl. IPv6), High Speed USB 2.0, WLAN¹⁾ (IEEE802.11b/g/n)

575 x 586 x 756 mm

~ 58 kg

Print Resolution

Page Description Languages Supported Systems

Print Functions

600 x 600 dpi

2,400 x 600 dpi with smoothing XPS, PCL6 and PostScript 3 compatible Windows 8/7/Vista/Server 2008/Server 2003 (32/64 bit), Windows Server 2012 R2/Server 2008 R2 (64 bit), Mac OS 10.4.11 - 10.9, Linux/UNIX,

Novell Netware (NDPS), Citrix, SAP, AS/400 Universal Driver, Driver templates, Driver plug-ins¹⁾, Hold print, Print from USB, Tandem printing,

AirPrint

Scan Resolution Scan Speed

Scan Modes **File Formats**

Scan Functions

Max. 600 x 600 dpi, 8 bit per colour channel

Colour/B&W: 43/57 ipm (300 dpi)
Auto-Colour (ACS), Colour, Greyscale, B&W
JPEG, Multi/Single Page TIFF/XPS/PDF, Secure
PDF, Slim PDF, Searchable PDF¹⁾ (and other
formats like DOCX, XLSX, RTF, TXT, PDF/A)¹⁾ Web Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local)

Meta Scan¹⁾, Scan to Box (e-Filing), WIA, TWAIN

Copy Resolution

First Copy Output Time Copy Modes

Scan: 600 x 600 dpi

Print: 2,400 x 600 dpi with smoothing

Approx. 3.7 seconds

25-400% (platen), 25-200% (RADF)¹⁾ Text, Text/Photo, Photo, Colour Document, Custom

Fax1) Communication Transmission Speed Compression

Fax Memory **Network-Fax**

Incoming Fax Routing

Super G3, G3 - (opt. 2nd line), Internet Fax T.37 Approx. 3 seconds per page JĖIG, MMR, MR, MH

GB (HDD) Transmission/Reception

Driver for Windows 8/7/Vista (32/64 bit), Windows Server 2012 R2/Server 2008 R2 (64 bit) To shared folders (SMB, FTP, IPX/SPX), E-Mail,

System & Security

Device Management

System Features

Accounting & Security

e-BRIDGE Fleet Management System¹⁾, TopAccess for remote administration and configuration e-Filing document server for secure storage. document distribution and Print-on-Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, Scan/Fax preview, e-BRIDGE Open Platform¹), Embedded Web Browser, Job Skip Role Based Access, LDAP support, 1,000 depart-ment codes & 10,000 user codes, card reader¹), private print, standard data encryption with Toshiba Secure HDD, Data Overwrite Enabler¹⁾, IP and MAC address filter, port filter, support of SSL and IPSec1) protocols, IEEE802.1x support, IEEE2600.1 compliant¹⁾, Scan to Secure PDF

Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m²

OPTIONS

RADF - MR-3028

100-sheet capacity, A5R-A3, 35-157 g/m²

JOB SEPARATOR TRAY - MJ-5006

2 inner trays, 150- and 250-sheet capacity

INNER FINISHER - MJ-1032N

2 trays, 600-sheet capacity 50-sheet multi-position stapling 482 x 508 x 232 mm (W x D x H), ~ 13 kg

MULTI-STAPLING FINISHER – MJ-1107

2 trays, 2,250-sheet capacity 50-sheet multi-position stapling $535 \times 598 \times 1,092 \text{ mm} (W \times D \times H), \sim 34 \text{ kg}$

SADDLE-STITCH FINISHER - MJ-1033

1 tray, 1,000-sheet capacity 50-sheet multi-position stapling Saddle-stitched booklets of up to 60 pages 409 x 624 x 961 mm (W x D x H), ~ 39 kg

SADDLE-STICH FINISHER - MJ-1108

2 trays, 3,250-sheet capacity 50-sheet multi-position stapling Saddle-stitched booklets of up to 60 pages 617 x 603 x 1,085 mm (W x D x H), ~70 kg

HOLE PUNCH UNIT -

MJ-6007 for Finisher MJ-1032N MJ-6008 for Finisher MJ-1033 MJ-6104 for Finisher MJ-1107/MJ-1108 Available in 2-holes (E), 4-holes (F/S)

PAPER FEED PEDESTAL - KD-1025

550-sheet (1 drawer), A5R-A3, 64-105 g/m² 668 x 701 x 291.5 mm (W x D x H), ~ 21 kg

LARGE CAPACITY FEEDER - KD-1026A4

2,000-sheet capacity, A4, 64-105 g/m² 668 x 737 x 292 mm (W x D x H), ~ 26 kg

OTHER OPTIONS

DESK - MH-2520 DRAWER MODULE - MY-1033 HDD 320 GB2 (FIPS 140-2 STD) - GE-1230 FAX BOARD - GD-1350EU WIRELESS LAN MODULE - GN-1060 e-BRIDGE ID-GATE - TWN3/4XX DATA OVERWRITE ENABLER - GP-1070 IPsec ENABLER - GP-1080 META SCAN ENABLER - GS-1010 UNICODE FONT ENABLER - GS-1007 ACCESSIBLE ARM - KK-2550 DAMP HEATER - MF-5070E

Optional

1GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed.

TOSHIBA TEC GERMANY **IMAGING SYSTEMS GMBH**