





Colour Manager

- High-speed multifunctional A3 system for enhanced quality colour document output.
- Large paper capacity for increased productivity.
- State-of-the-art security technology protects confidential data.
- Large user interface and intuitive operation help optimise workflows.
- Equipped with energy saving features for environmentally friendly operation.



е-studio 5560 с е-studio 6560 с е-studio 6570 с













General

OPTIONS MULTI-STAPLING FINISHER - MJ-1103 2 trays, 3,250-sheet capacity 50-sheet multi-position stapling A5R-A3, 64-105 g/m² (stapling mode) 617 x 603 x 1,085 mm (W x D x H), ~ 40 kg countries. All SADDLE-STITCH FINISHER - MJ-1104 2 trays, 3,250-sheet capacity or notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or some models may change in the time between the production and the release of this documentation. Copyright © 2014 TOSHIBA TEC. 50-sheet multi-position stapling 5-sheet center-folding Saddle-stitched booklets of up to 60 pages A5R-A3, 64-105 g/m² (stapling mode) 617 x 603 x 1,085 mm (W x D x H), \sim 70 kg **HOLE PUNCH UNIT - MJ-6102** Option for Finisher MJ-1103/MJ-1104 Available in: 2 holes (E), 4 holes (F), 4 holes (S) 112 x 573 x 323 mm (W x D x H), \sim 7 kg LARGE CAPACITY FEEDER - MP-2501A 2,500-sheet capacity, A4, 64-256 g/m² 360 x 552 x 542 mm (W x D x H), ~ 29 kg **OTHER OPTIONS** SIDE EXIT TRAY - KA-6550-ET HDD 320 GB2 (FIPS 140-2 STD) - GD-1230 FAX BOARD - GD-1270FU-FN WIRELESS LAN MODULE - GN-1060 e-BRIDGE ID-GATE - TWN3/4XX DATA OVERWRITE ENABLER - GP-1070 IPsec ENABLER - GP-1080 META SCAN ENABLER - GS-1010 UNICODE FONT ENABLER - GS-1007 product complies with IEC60825-1. Technical data is subject to change without prior making efforts to deliver the latest status of data to our partners. Specifications for so 1 GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed. e-STUDIO5560c only With Toshiba Waterproof banner paper up to 230g/m² PostScript driver only Productivity and paper specifications are related to a paper

Print & Copy Speed Colour: 55/65/65 ppm (A4), 27/30/30 ppm (A3) B&W: 55/65/75 ppm (A4), 27/30/37 ppm (A3) Warm-up Time Approx. 70 seconds from low-power mode Cassettes: A5R-320 x 460 mm, 64-256 g/m² Paper Size & Weight Tandem LCF³:A4, 64-256 g/m² Bypass: A6R-330 x 483 mm, 64-300 g/m²

banner paper (up to 313 x 1,200 mm, 90-163 g/m²)4) **Paper Capacity** 4 x 540 sheets (Cassettes) or 2 x 540 sheets (Cassettes) + 2,320 sheets (Tandem LCF)³, 100 sheets³ (Bypass) Max. 6,000 sheets with external LCF¹) A5R-320 x 460 mm, 64-256 g/m²

Automatic Duplex Controller Type Toshiba e-BRIDGE

Memory

Toshiba Secure HDD 320 GB2, 2.0 GB RAM Interface 10/100/1000 BaseT (incl. IPv6), High-Speed USB 2.0, WLAN¹⁾ (IEEE802.11b/g/n)

600 x 600 dpi, 8 bit per colour channel

1,200 x 1,200 dpi, 2 bit per colour channel⁵⁾

Dimensions (W x D x H) 980 x 698 x 1,540 mm ~ 244 kg Weight

Print Resolution **Page Description Languages** Supported Systems

XPS, PCL6 and PostScript 3 compatible
Windows 8/7/Vista/Server 2008/Server 2003
(32/64 bit), Windows Server 2012 R2/Server 2008
R2 (64 bit), Mac OS X 10.4.11-10.9, Linux/UNIX,
Novel Netware (NDPS), Citrix, SAP, AS/400 Colour Modes Auto-Colour (ACS), Colour, Twin Colour, B&W **Colour Settings** ICC profiles management, Brightness, Saturation,

Contrast, Colour Balance Universal Driver, Driver templates, Driver plug-ins¹⁾, Hold print, Print from USB, Tandem printing, AirPrint **Print Functions**

Scan Resolution Scan Speed **Document Feeder** Scan Modes File Formats

Colour & B&W: up to 77 ppm (300 dpi) Max. 100 sheets, A5R-A3, 35-209 g/m² Auto-Colour (ACŚ), Colour, Greyscale, B&W JPEG, Multi/Single Page TIFF/XPS/PDF, Secure PDF, Slim PDF, Searchable PDF¹⁾ (and other editable formats like DOCX, XLSX, RTF, TXT, PDF/A)¹¹ WS Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local), Meta Scan¹⁾, Scan to Box (e-Filing), WIA, TWAIN

Max. 600 x 600 dpi, 8 bit per colour channel

Resolution Copy **First Copy Output Time**

Scan Functions

600 x 600 dpi, 10 bit per colour channel 600 x 600 dpi, 8 bit per colour channel Scan: Print: 2,400 x 600 dpi, B&W with smoothing Colour: approx. 6.5 seconds

B&W: approx. 5.3/5.3/4.6 seconds 25-400% (platen), 25-200% (RADF) Text, Text/Photo, Photo, Printed Image, Map, Zoom Copy Modes Image Smoothing Auto-Colour (ACS), Full Colour, Twin Colour, Mono Colour, B&W **Colour Modes**

Hue, Saturation, Colour Balance, RGB Adjustment, **Colour Settings**

Super G3, G3 (opt. 2nd line), Internet Fax T.37 Fax1) Communication Approx. 3 seconds per page JBIG, MMR, MR, MH Transmission Speed Compression Driver for Windows 8/7/Vista (32/64 bit), Network-Fax

Server 2012 R2/Server 2008 R2 (64 bit) **Incoming Fax Routing** To shared folders (SMB, FTP, IPX/SPX), E-mail,

System Device Management & Security

for remote administration and configuration **System Features** e-Filing document server for secure storage. document distribution and Print-on-Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, Scan/Fax preview, RIP-while-Print,

e-BRIDGE Open Platform¹⁾, Embedded Web Browser, Job Skip

Accounting & Security Role Based Access, LDAP support, 1,000 department codes & 10,000 user codes, card reader¹⁾, private print, standard data encryption with Toshiba Secure HDD, Data Overwrite Enabler¹⁾, IP and MAC address filter, port filter, support of SSL and IPsec¹⁾ protocols, IEEE802.1x support,

IEEE2600.1 compliant¹⁾, Scan to secure PDF

e-BRIDGE Fleet Management System¹⁾, TopAccess

TOSHIBA TEC GERMANY **IMAGING SYSTEMS GMBH**

CARL-SCHURZ-STRASSE 7 · D-41460 NEUSS TEL. +49(0)2131-12450, FAX +49(0)2131-1245402 WWW.TOSHIBA-EUROPE.COM/TEC



size of A4 and a paper weight of 80 g/m2 if not otherwise

Optional

s Class 1 laser p are constantly r

This We