





Document Manager

- Highly productive monochrome systems with outstanding quality
- Security enhanced systems featuring Toshiba's innovative secure hard disc drive
- Efficient multifunctionality including high-resolution colour scan
- Sophisticated options for professional document finishing
- Effective power save mode to help save costs and resources

E-STUDIO 556SE
E-STUDIO 756SE
E-STUDIO 856SE















ESTUDIO 556SE ESTUDIO 756SE C STUDIO 656SE STUDIO 856SE



General
Print
Scan

55/65/75/85 ppm (A4) 34/37/40/43 ppm (A3) Approx. 130 seconds **Print & Copy Speed** Warm-up Time Paper Size & Weight

Cassettes: A5R-A3, 64-209 g/m² Tandem LCF: A4, 64-209 g/m² Large Capacity Feeder¹⁾: A4, 64-209 g/m² Bypass: A5R-A3, 64-209 g/m² 2 x 500 sheets (Cassettes), 2,500 sheets A4 (Tandem LCF), 100 sheets (Bypass)

Maximum: 7,600 sheets A5R-A3, 64-209 g/m² Toshiba e-BRIDGE

9" (22.8 cm) colour LCD touch screen Toshiba Secure HDD 160 GB², 1 GB RAM 10/100/1000 BaseT (incl. IPv6), High Speed USB 2.0, WLAN³ (IEEE802.11b/g), Bluetooth³ 698 x 789 x 1,176 mm (W x D x H), ~ 203 kg

Dimensions & Weight

Resolution Page Description Languages Supported Systems

Paper Capacity

Automatic Duplex

Controller Type

Print Functions

Scan Functions

Control Panel

Memory

Interface

Max. 2,400 x 600 dpi with smoothing XPS, PCL6 and PostScript 3 compatible Windows 7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Windows Server 2008 R2 (64 bit), Mac OS X, Linux/UNIX, Novell Netware (NDPS), Citrix, SAP, AS/400

Universal Driver, Driver templates, Driver plug-ins, Private/Hold print, Print from USB, Tandem printing,

Max. 600 x 600 dpi, 8 bit per colour channel

Resolution Scan Speed **Document Feeder** Scan Modes File Formats

Colour & B&W: up to 77/80 ipm (300 dpi) Max. 100 sheets, A5R-A3, 35-209 g/m² Auto-Colour (ACS), Colour, Greyscale, B&W
JPEG, Multi/Single Page TIFF/XPS/PDF, Secure
PDF, Slim PDF, Searchable PDF¹⁾ (and other formats
like DOC, XLS, RTF, TXT, PDF/A)¹⁾ WS Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS

IPX/SPX, local), Meta Scan¹⁾, Scan to Box (e-Filing), TWAIN 1.7/1.8/1.9

Copy Resolution **First Copy Output Time** Copy Modes

Scan: 600 x 600 dpi Print: 2,400 x 600 dpi with smoothing

Approx. 3 seconds per pagé

Approx. 4/4/3.5/3.5 seconds 25-400% (platen), 25-200% (RADF)

Text, Text/Photo, Photo, Colour Document, Custom

Fax1) Communication Transmission Speed Compression Fax Memory **Network-Fax**

JĖİG, MMR, MR, MH 1 GB (HDD) Transmission/Reception Driver for Windows 7/Vista/XP (32/64 bit), etc. To shared folders (SMB, FTP, IPX/SPX), E-mail, e-Filing

Super G3, G3 - (opt. 2nd line), Internet Fax T.37

Incoming Fax Routing

System & Security

Device Management

Accounting & Security

System Features

e-BRIDGE Fleet Management System¹⁾, TopAccess for remote administration and configuration

e-Filing document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, RIP-while Print, e-BRIDGE Open Platform¹⁾, Embedded Web Browser, Job Skip Role Based Access, LDAP support, 1,000 department codes & 10,000 user codes, card reader¹⁾, Quota management, standard data encryption with

Toshiba Secure HDD, Data Overwrite Enabler IP and MAC address filter, port filter, support of SSL and IPsec¹⁾ protocols, IEEE802.1x support, IEEE2600.1 compliant¹⁾, Scan to Secure PDF

Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m² if not

OPTIONS

MULTI-STAPLING FINISHER - MJ-1027 2 trays, 4,000-sheet capacity

50-sheet multi-position stapling 616 x 630 x 1,023 mm (W x D x H), ~ 43 kg

SADDLE-STITCH FINISHER - MJ-1028

2 trays, 4,000-sheet capacity 50-sheet multi-position stapling Saddle-stitched booklets of up to 60 pages 616 x 630 x 1,023 mm (W x D x H), ~ 63 kg

SADDLE-STITCH FINISHER - MJ-1029

2 trays, 4,000-sheet capacity 100-sheet multi-position stapling Saddle-stitched booklets of up to 60 pages 616 x 630 x 1,023 mm (W x D x H), ~ 66 kg

HOLE PUNCH UNIT - MJ-6003

Option for Finisher MJ-1027/1028/1029 Available in 2 holes (E), 4 holes (F/S) 76 x 615 x 275 mm (W x D x H), \sim 5.4 kg

INSERTER UNIT - MJ-7001

Option for Finisher MJ-1027/1028/1029 1 tray, 100-sheet capacity Sheet/Cover Insertion, Manual finishing A4-A3, 60-256 g/m² 533 x 612 x 1,072 mm (W x D x H), ~ 20 kg

LARGE CAPACITY FEEDER - MP-4004A

4,000-sheet capacity, A4, 64-209 g/m² $327 \times 604 \times 617 \text{ mm}$ (W x D x H), ~ 37 kg

OTHER OPTIONS

FAX BOARD - GD-1250EU-F DATA OVERWRITE ENABLER - GP-1070 e-BRIDGE ID-GATE - KP-2004/5, TWN3XX WIRELESS LAN MODULE - GN-1060 BLUETOOTH MODULE - GN-2020 META SCAN ENABLER - GS-1010 IPsec ENABLER - GP-1080 UNICODE FONT ENABLER - GS-1007 e-BRIDGE RE-RITE - GB-1280 DAMP HEATER KIT - MF-6560E

- Optional
- ²⁾ 1 GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed.

Г

 \Box

TOSHIBA TEC GERMANY **IMAGING SYSTEMS GMBH**

