

Registered Office:

10 broughton Way, Whitehills Business Park, Blackpool FY4 5QN

30 Student Classroom Cart **Specifications**

STUDENT DEVICES (Google Pixel 2 XL)

Operating system

Android 11

System architecture/processor

Qualcomm Snapdragon 835 MSM8998 (10 nm) CPU - Octa-core (4x2.35 GHz Kryo & 4x1.9 GHz Kryo)

GPU - Adreno 540

Memory (RAM) 4GB LPDDR4

Storage (ROM)

128GB

Dimensions

Height: 157.9mm Width: 76.7mm Depth: 7.9mm

Weight 175g

Display

6.0 inches, 92.6 cm2 (~76.4% screen-to-body ratio) 1440 x 2880 pixels, 18:9 ratio (~538 ppi density)

Corning Gorilla Glass 5

TEACHER DEVICE (Lenovo Tab 4 Plus 10) 247 x 171 x 8.3 mm

Product Dimensions

Screen Size 10.1 inches

Screen Resolution 1920 x 1200 pixels

Multi-touch Capacitive-type multi-touch, support 10-point touch Oualcomm MSM8917 Snapdragon 425 (28 nm) (Wi-Fi/LTE model) **Battery**

Li-lon 3520 mAh, non-removable 10.5W wired (capped), PD2.0

12.2 MP, f/1.8, 27mm (wide), 1/2.55", 1.4µm, dual pixel PDAF, Laser AF,

Camera Features

Dual-LED flash, HDR, panorama

4K@30fps (gyro-EIS), 1080p@30/60/120fps (gyro-EIS), 720p@240fps (gyro-EIS)

Front camera

8 MP, f/2.4, 25mm (wide), 1/3.2", 1.4µm, HDR

Connectivity

Type-C (reversible), USB 3.1

Bluetooth® technology 5.0, A2DP, LE, aptX HD

Processor Count RAM Size 2 GB

Maximum Memory Supported 64 GB

Storage 16 GB

Hard Disk Technology



Wi-Fi 802.11 a/b/g/n/ac, dual-band, Wi-Fi Direct, DLNA

Speakers/microphones

Front ported loud speaker Mic

Sensors

Fingerprint (rear-mounted) accelerometer

gyro proximity

compass

barometer

DUAL BAND ROUTER (Asus RT-51U)

Powered by 5th generation Wi-Fi (5G Wi-Fi), the 802.11ac chipset gives the RT-AC51U faster wireless speeds than N technology.

At 2.4 GHz, it reaches 300 Mbps, while on the 5GHz band it blazes to 433 Mbps. The upgraded bandwidth has the higher capacity you need to increase Wi-Fi enjoyment.

Twin detachable antennas allow for better alignment and stronger antenna upgrades.

Faster transfer speeds with Gigabit network ports SPI Firewall with IP and MAC address filtering

One touch wireless encryption with WPS button

Connections: 1x RJ45 WAN, 4x RJ45 LAN, x USB Dimensions (HxWxD): 36 x 189 x 129mm

iNCHARGE CASE (C87)

VR cases and Parotec speciÿcations of electrics. Parotec Approvals: **CE** Approved

ISO 9001 registered (2008)

Solutions based around our 16 & 36 x Port PCB Intelligence Board have been subject to testing at Cass Industries Limited an compliance testing and CE marking partner for UK & EU requirements.

Parotec PCB Boards:

PCB Inner board Power consumption: 5V @ 34A maximum supply (each port is current limited to 2.1A) Robust design with up to 35 possible ÿxing holes on uniform 25mm centres IEC/EN 60335 compliant and CE certiyed Input voltage required up to 5.3V

Charge & Sync version of PCB also UL (USA) approved

*Charge Only boards currently used for VR kits. IF sending to US we would add Charge & Sync PCB's.

Parotec: Explorer Cases. Used to house all VR Kit.

Where no modiÿcation to the physical case is made these are fully waterproof and dust free.

Where we may have added external cooling fans the cases are reduced to weather proof and dust free.

